

# Helitak

## FT10000 Boeing CH-47 Chinook

Design & Manufacturing  
of Aerial Fire Fighting  
Suppression Systems



### Tank Capacity

10000Ltrs (2645Gal)



### Tank Weight Empty

920Kgs (2030Lbs)



### Tank Weight Full

11000Kgs (24250Lbs)



### Foam/Retardant Capacity

500Ltrs (132Gal)



### Power Requirements

40Kva 110Vac 3 Phase

50Amps

28Vdc 30amps



### Hover Fill Pump

Helitak HP10000

12000Ltrs (3200Gal) pm

Fills 60 seconds



### Tank Height

360mm (14 Inch)

- Helitak Live Microprocessor Controller  
With programmable multi and partial drops  
(Full, 1/2, 1/3, 1/4 Drops plus variable application rates)
- User Friendly cyclic controller
- Carbon Fibre Epoxy Resin
- Internal Control and electrical compartment
- Failsafe emergency Door Operation
- 25 Minutes Install – Roll Under, Bolt On,
- Plug and Play
- Hover Pump and/or Sea Snorkel
- Tank Length 6500mm (21.3 Ft)
- Tank Width 2200mm (7.2 Ft)
- DESIGNED FOR MAXIMUM HEAD PRESSURE FOR MOST  
EFFECTIVE CANOPY PENETRATION AVAILABLE IN THE MARKET



12 Leo Alley Road  
Noosaville, Queensland  
AUSTRALIA, 4566  
+ 61 400 350 205  
sales@helitak.com.au  
www.helitak.com.au



# Helitak

firefightingequipment

