

Helitak

FT1300 Airbus AS350, H125

Design & Manufacturing
of Aerial Fire Fighting
Suppression Systems



Tank Capacity
1000Ltrs (264Gal)
1300Lts (343Gal)



Tank Weight Empty
105Kgs (231Lbs)



Tank Weight Full
1405Kgs (3097Lbs)



Foam/Retardant Capacity
95Ltrs (25Gal)



Power Requirements
28Vdc 150Amps



Hover Fill Pump
Helitak HP2000
2000Ltrs (528Gal) pm
Fills 35 seconds



Tank Height
270mm (11 Inch)

- Heliak Programmable Logic Controller (PLC) controls and records variable application rates, water collection and delivery GPS, maintenance and operations data telemetry
- User Friendly Cyclic Controller
- Carbon Fibre Epoxy Resin Shell construction
- Internal control and electrical compartment
- Failsafe emergency Door Operation
- 25 Minutes Install/Removal - Roll Under, Attach Mounting Pins and Electrical Plugs - Plugs and Play
- Tank Length 2000mm (6.56 Feet), Width 1200mm (47" Inches)
- DESIGNED FOR MAXIMUM HEAD PRESSURE FOR MOST EFFECTIVE CANOPY PENETRATION AVAILABLE IN THE MARKET



12 Leo Alley Road
Noosaville, Queensland
AUSTRALIA, 4566
+ 61 400 350 205
sales@helitak.com.au
www.helitak.com.au

Helitak

firefighting equipment

