

Helitak

FT1800 - FT2500 Bell Medium

Design & Manufacturing
of Aerial Fire Fighting
Suppression Systems



Tank Capacity

1800Ltrs - 2500Ltrs
(475 - 660Gal)



Tank Weight Empty

146Kgs (321Lbs)



Tank Weight Full

1946 - 2646Kgs
(4290 - 5820Gal)



Foam/Retardant Capacity

95Ltrs (25Gal)



Power Requirements

28Vdc 150Amps



Hover Fill Pump

Helitak HP2000
2000Ltrs (528Gal) pm
Fills 35 seconds



Tank Height

270mm (11 Inch)

- Helitak Programmable Logic Controller (PLC) controls and records variable application rates, water collection and delivery GPS, maintenance and operations data telemetry
- User Friendly Cyclic Controller
- Carbon Fibre Epoxy Resin Shell construction
- Internal control and electrical compartment
- Failsafe emergency Door Operation
- 25 Minutes Install/Removal - Roll Under, Attach Mounting Pins and Electrical Plugs - Plugs and Play
- Tank Length 2600mm (8.5 Feet), Width 1740mm (5.7 Feet)
- DESIGNED FOR MAXIMUM HEAD PRESSURE FOR MOST EFFECTIVE CANOPY PENETRATION AVAILABLE IN THE MARKET



12 Leo Alley Road
Noosaville, Queensland
AUSTRALIA, 4566
+ 61 400 350 205
sales@helitak.com.au
www.helitak.com.au

Helitak

firefighting equipment

