

Helitak

FT2800 Leonardo Agusta

AW139, AW169, AW189

Design & Manufacturing
of Aerial Fire Fighting
Suppression Systems



Tank Capacity

2800Ltrs (739Gal)



Tank Weight Empty

185Kgs (407Lbs)



Tank Weight Full

2985Kgs (6580Lbs)



Foam/Retardant Capacity

150Ltrs (39Gal)



Power Requirements

28Vdc 150Amps



Hover Fill Pump

Helitak HP2000
2000Ltrs (528Gal) pm
Fills 65 seconds



Tank Height

300mm (12Inch)

- Helitak Programmable Logic Controller (PLC) controls and records variable application rates, water collection and delivery GPS, maintenance and operations data telemetry
- User Friendly Cyclic Controller
- Carbon Fibre Epoxy Resin Shell construction
- Internal control and electrical compartment
- Failsafe emergency Door Operation
- 25 Minutes Install/Removal - Roll Under, Attach Mounting Pins and Electrical Plugs - Plugs and Play
- Tank Length 2600mm (8 Feet), Width 1840mm (6 Feet)
- DESIGNED FOR MAXIMUM HEAD PRESSURE FOR MOST EFFECTIVE CANOPY PENETRATION AVAILABLE IN THE MARKET



12 Leo Alley Road
Noosaville, Queensland
AUSTRALIA, 4566
sales@helitak.com.au
www.helitak.com.au

