

Helitak

FT4250 Airbus Super Puma AS332, H215, H225 Firecat



Tank Capacity
4250Ltrs (1122Gal)



Tank Weight Empty
325Kgs (716Lbs)



Tank Weight Full
4575Kgs (9369Lbs)



Foam/Retardant Capacity
205Ltrs (54Gal)



Power Requirements
20Kva 110Vac 3 Phase
35Amps
28Vdc 30Amps



Hover Fill Pump
Helitak HP6000
6000Ltrs (1585Gal) pm
Fills 46 seconds



Tank Height
300mm (12Inch)

- Helitak Programmable Logic Controller (PLC) controls and records variable application rates, water collection and delivery GPS, maintenance and operations data telemetry
- User Friendly Cyclic Controller
- Carbon Fibre Epoxy Resin Shell construction
- Internal control and electrical compartment
- Failsafe emergency Door Operation
- 25 Minutes Install/Removal - Roll Under, Attach Mounting Pins and Electrical Plugs - Plugs and Play
- Tank Length 3400mm (11 Feet), Width 2000mm (6.5 Feet)
- DESIGNED FOR MAXIMUM HEAD PRESSURE FOR MOST EFFECTIVE CANOPY PENETRATION AVAILABLE IN THE MARKET



12 Leo Alley Road
Noosaville, Queensland
AUSTRALIA, 4566
sales@helitak.com.au
www.helitak.com.au



Helitak

firefighting equipment

