

# Helitak

## FT4500 Sikorsky Black Hawk UH60, S70



**Tank Capacity**  
4500Ltrs (1188Gal)



**Tank Weight Empty**  
325Kgs (716Lbs)



**Tank Weight Full**  
4825Kgs (10637Lbs)



**Foam/Retardant Capacity**  
205Ltrs (54Gal)



**Power Requirements**  
20Kva 110Vac 3 Phase  
50Amps  
28Vdc 30Amps



**Hover Fill Pump**  
Helitak HP6000  
6000Ltrs (1585Gal) pm  
Fills 46 seconds



**Tank Height**  
300mm (12Inch)

- Heliak Programmable Logic Controller (PLC) controls and records variable application rates, water collection and delivery GPS, maintenance and operations data telemetry
- User Friendly Cyclic Controller
- Carbon Fibre Epoxy Resin Shell construction
- Internal control and electrical compartment
- Failsafe emergency Door Operation
- 25 Minutes Install/Removal - Roll Under, Attach Mounting Pins and Electrical Plugs - Plugs and Play
- Tank Length 3400mm (11 Feet), Width 2000mm (6.5 Feet)
- Lower ESSS Mount Required
- DESIGNED FOR MAXIMUM HEAD PRESSURE FOR MOST EFFECTIVE CANOPY PENETRATION AVAILABLE IN THE MARKET



12 Leo Alley Road  
Noosaville, Queensland  
AUSTRALIA, 4566  
+ 61 400 350 205  
sales@helitak.com.au  
www.helitak.com.au

# Helitak

firefighting equipment

